| NOCURPR | 24° MIN FP OF PAVEMI STEEL PI SEE NOT STREET TYPICAL | | 24' MIN FROM PROPERTY INE OF EDGE OF RIGHT OF WAY | AIR & VACUUM VALVE ENCLOSURE TYPICAL, SEE NOTE 2 CONCRETE PAD TYPICAL ALTERNATE LOCATION SIDEWALK (TYPICAL) CONCRETE PAD TYPICAL CONCRETE PAD TYPICAL |
|---|---|------|---|--|
| CONTIGUOUS CONTIGUOUS SIDEWALK | | | | |
| 1) PROTECTION POSTS SHALL BE INSTALLED AS CALLED FOR ON THE PLANS OR AS DIRECTED BY THE ENGINEER | | | | |
| 2) AN EASEMENT MAY BE NEEDED DEPENDING ON LOCATION OF ENCLOSURE | | | | |
| 3) IF THE CONCRETE SLAB IS TO BE INSTALLED ADJACENT TO A CONCRETE SIDEWALK A COLD JOINT STRIP SHALL BE INSTALLED | | | | |
| 4) MATERIALS SHALL BE SELECTED FROM THE APPROVED MATERIALS LIST | | | | |
| REVISIONS | APPROVED | DATE | VISTA IRRIGATION DISTRICT | B. S. M. W. |
| | | | AIR & VACUUM VALVE ENCLOSURE LOCAT | 10120000000000000000000000000000000000 |